ORDERING CHART
4 & 6-ROW

HMM	058	FDE	1	X	99	E	4	00

Series

Contact Capacity
(Use All 3 Places)

Body Style	
Receptacle	
FAE	Stacking
FBE	Flex Cable
FDE	Dip Solder Straight
FEE	Dip Solder Right Angle
FSE	Solder Cup
FVE	Compliant
FWE	Wire Wrap
Plug	
MAE	Stacking
MBE	Flex Cable
MDE	Dip Solder Straight
MSE	Solder Cup
MVE	Compliant
Plug (Low Profile)	
MEE	Dip Solder Right Angle
MRE	Surface Mount
RBE	Flex Cable
RDE	Dip Solder Straight
RSE	Solder Cup

Termination Length - "L"			
Code	Dip Solder	Wire Wrap	Flex
1	.109	.375	.050
2	.140	.500	.098
3	.172	.625	-
4	.234	-	-
9	User Defined		
0	Use For Solder Cup & Compliant Without Extension		
A	Use For Compliant With Stacking Extension		

Variation Code - Factory Assigned	
20	Solder Dip Terminals
C0	Epoxy Termination Sealed
C2	Epoxy Sealed & Solder Dipped

Row Designation	
4	4 Row Series
6	6 Row Series

Mounting Style	
C	Threaded Insert
E	Threaded Stud
0	No Mount Provision
Check Factory. Not All Styles Are Available In All Configurations.	

Hardware Arrangement	
00	No Hardware
01 - 36	Y - "D" Shaped Guide
65 - 68	Universal - See Appendix
69 - 72	See Appendix
97	2 Pin Guides Unassembled
98	2 Socket Guides Unassembled
99	1 Pin & Socket Unassembled

Hardware Style	
A	Round Guides w/ Mtg. Stud
B	"D" Shaped Guides w/ Mtg. Stud (Polarizing)
H	Short Rotating (Int. Hex)
K	Fixed Locking
T	Fixed Locking w/ Mtg. Stud
X	Round Guides
Y	"D" Shaped Guides (Polarizing)
0	No Hardware Supplied