

TERMINATION STYLES - 3 ROW RECEPTACLE HARDWARE OMITTED FOR CLARITY

<p>F AE9 STACKING</p>		<p>FVEA COMPLIANT STACKING</p>																				
<p>FBE FLEX CABLE</p>		<p>FDE DIP SOLDER</p>																				
<p>FVE COMPLIANT</p>		<p>FWE WIRE WRAP</p>																				
<p>FSE SOLDER CUP</p>		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>CONNECTOR</th> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>HGM[050-104]</td> <td>Ø .039 X.090 DEEP</td> <td>0.18</td> <td>0.055</td> </tr> <tr> <td>HGM122</td> <td>Ø .039 X.090 DEEP</td> <td>0.15</td> <td>0.055</td> </tr> <tr> <td>HGM160</td> <td>Ø .035 X.090 DEEP</td> <td>0.10</td> <td>0.045</td> </tr> <tr> <td>HGM208</td> <td>Ø .035 X.090 DEEP</td> <td>0.10</td> <td>0.045</td> </tr> </tbody> </table>	CONNECTOR	A	B	C	HGM[050-104]	Ø .039 X.090 DEEP	0.18	0.055	HGM122	Ø .039 X.090 DEEP	0.15	0.055	HGM160	Ø .035 X.090 DEEP	0.10	0.045	HGM208	Ø .035 X.090 DEEP	0.10	0.045
CONNECTOR	A	B	C																			
HGM[050-104]	Ø .039 X.090 DEEP	0.18	0.055																			
HGM122	Ø .039 X.090 DEEP	0.15	0.055																			
HGM160	Ø .035 X.090 DEEP	0.10	0.045																			
HGM208	Ø .035 X.090 DEEP	0.10	0.045																			
<p>FEE DIP SOLDER RIGHT ANGLE</p>		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>CONNECTOR</th> <th>A</th> <th>B</th> </tr> </thead> <tbody> <tr> <td>HGM[050-104]</td> <td>0.200</td> <td>0.120</td> </tr> <tr> <td>HGM122</td> <td>0.240</td> <td>0.125</td> </tr> <tr> <td>HGM160</td> <td>0.200</td> <td>0.120</td> </tr> <tr> <td>HGM208</td> <td>0.200</td> <td>0.120</td> </tr> </tbody> </table>	CONNECTOR	A	B	HGM[050-104]	0.200	0.120	HGM122	0.240	0.125	HGM160	0.200	0.120	HGM208	0.200	0.120					
CONNECTOR	A	B																				
HGM[050-104]	0.200	0.120																				
HGM122	0.240	0.125																				
HGM160	0.200	0.120																				
HGM208	0.200	0.120																				